

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

No. FB750 – 20210107

1. **Unique identification code of the product-type:** Nullifire FB750 Intubatt

Intended use/es: A mineral wool board coated on both faces used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.

3. **Manufacturer:** TREMCO CPG UK Limited, Coupland Road, Hindley Green, Wigan. WN24HT

5. **System/s of AVCP:** System 1

6. **European Assessment Document:** EAD 350141-00-1106

European Technical Assessment: ETA 20/1319

Technical Assessment Body: ETA-Danmark A/S

Notified body/ies: CPR Notified Body DBI Certification A/S No. 2531

7. **Declared performance/s**

Basic Work Requirement	Performance
Mechanical resistance and stability	
None	Not relevant
Safety in case of fire	
Reaction to fire (EN 13501-1)	Class E
Resistance to fire (EN 13501-2)	See ETA 20/1319 Annex A
Hygiene, Health and the Environment	
Air Permeability (EN 1026:2000)	See ETA 20/1319 Annex B
Water Permeability (EAD 350141-00-1106 Annex C)	NPD
Release of dangerous substances	Declaration of manufacturer – Uses categories IA3, S/W3
Safety in Use	
Mechanical Resistance and stability (EOTA TR001:2003)	NPD
Resistance to Impact / movement (EOTA TR001:2003)	NPD
Adhesion (EOTA TR001:2003)	NPD
Protection against noise	
Airborne Sound Insulation (EN10140-2 / EN ISO 717-1)	See ETA 20/1319 Annex C
Energy, Economy and Heat Retention	
Thermal Properties (EN 12664, EN 12667 or EN 12939)	NPD
Water vapour permeability (EN ISO 12572 / EN 12086)	NPD
General Aspects Relating to fitness for use	
Durability and Serviceability (EOTA TR 024:2009)	Z ₁

NPD = No Performance Determined

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Operations Director



At Wigan on 7 January 2021

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

2.

CE	
TREMCO CPG UK Limited Coupland Road, Hindley Green, Wigan, WN2 4HT 21 2531-CPR-CX010106 FB750 – 20210107 www.nullifire.com/FB750	
EN 1366 Part 3 ETA 20/1319 EAD 350141-00-1106 Part 2	
A mineral wool board coated on both faces used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.	
Essential Characteristic	Performance
Safety in Case of Fire	
Reaction to fire	Class E
Resistance to fire	ETA 20/1319 Annex A
Hygiene, Health and Environment	
Air Permeability	ETA 20/1319 Annex B
Water Permeability	NPD
Dangerous Substances	Uses categories IA3, S/W3
Safety in use	
Mechanical resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
Protection against noise	
Airborne sound insulation	ETA 20/1319 Annex C
Energy, Economy and Heat Retention	
Thermal properties	NPD
Water vapour permeability	NPD
General aspects relating to fitness for use	
Service & Durability	Z ₁